

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**Aerosol - Lubricating agent
Professional uses**1.3. Details of the supplier of the safety data sheet**

Company name:	innotech-Vertriebs GmbH	
Street:	Junkerstrasse 16	
Place:	D-93055 Regensburg	
Telephone:	+49 (0) 941 70 08 78	Telefax: +49 (0) 941 70 46 60
e-mail:	info@innotech-r.de	
Contact person:	Mr. Massen	
Internet:	www.innotech-r.de	
Responsible Department:	sales department	

1.4. Emergency telephone number: +49 (0) 941 70 08 78
Only available during office hours.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Aerosol: Aerosol 1
Aspiration hazard: Asp. Tox. 1
Specific target organ toxicity - repeated exposure: STOT RE 1
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
May be fatal if swallowed and enters airways.
Causes damage to organs through prolonged or repeated exposure.
Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Signal word: Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 2 of 12

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P314	Get medical advice/attention if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with local/regional/national/international regulation.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)			25 - < 30 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			25 - < 30 %
	919-164-8		01-2119473977-17	
	STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H372 H304 H412 EUH066			
106-97-8	butane			20 - < 25 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane			10 - < 12.5 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics			5 - < 10 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
68937-41-7	Isopropylphenyl phosphate			0.1 - < 0.5 %
	273-066-3		01-2119535109-41	
	Repr. 2, STOT RE 2, Aquatic Chronic 2; H361fd H373 H411			
61791-55-7	N-Tallow propylene diamine			0.1 - < 0.5 %
	263-189-0		01-2119487014-41	
	Acute Tox. 4, Skin Corr. 1B, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 2; H302 H314 H372 H400 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 3 of 12

4.1. Description of first aid measures**General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 4 of 12

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Aerosol - Lubricating agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics			
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

8.2. Exposure controls



Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 5 of 12

technical means. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. When using do not eat, drink or smoke.

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: Eye glasses with side protection DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. DIN EN 374

Suitable material: Butyl caoutchouc (butyl rubber) (0,5 mm), Breakthrough time (maximum wearing time): 240 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus:

Combination filtering device (EN 14387) A-P2

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light yellow
Odour:	like: Mineral oil
pH-Value:	not applicable

Changes in the physical state

Melting point:	not relevant
Initial boiling point and boiling range:	< -20 °C
Flash point:	< -20 °C
Sustaining combustion:	No data available

Flammability

Solid:	not relevant
Gas:	not relevant

Explosive properties

In use may form flammable/explosive vapour-air mixture.

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	15 vol. %
Ignition temperature:	> 200 °C

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	not relevant
----------------------------	--------------

Oxidizing properties

Not oxidising.

Vapour pressure:	not determined
------------------	----------------

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 6 of 12

Density (at 20 °C):	0,68 g/cm ³
Water solubility: (at 20 °C)	practically insoluble
Solubility in other solvents	
not relevant	
Partition coefficient:	not determined
Viscosity / kinematic:	not applicable
Vapour density:	not relevant
Evaporation rate:	not relevant

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)				
	oral	LD50 > 15000 mg/kg	Rat	OECD Guideline 423	
	dermal	LD50 >= 3160 mg/kg	Rabbit	OECD Guideline 402	
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat	OECD 403	
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >3400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 (13,1) mg/l	Rat		
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2800 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >23,3 mg/l	Rat		
68937-41-7	Isopropylphenyl phosphate				
	dermal	LD50 > 10000 mg/kg	Rabbit	16 CFR 1500. 40	
61791-55-7	N-Tallow propylene diamine				
	oral	ATE 500 mg/kg			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking. Causes damage to organs through prolonged or repeated exposure. (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	OECD Guideline 202
	Fish toxicity	NOEC mg/l	(0,101)	28 d	Oncorhynchus mykiss	ECHA
	Crustacea toxicity	NOEC mg/l	(0,176)	21 d	Daphnia magna	ECHA
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)					
	Acute fish toxicity	LC50 mg/l	10-100	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	50-100	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	10-22	48 h	Daphnia magna (Big water flea)	
106-97-8	butane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Enviro
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Asse
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	147,54	96 h	Fish, no other information	United States Enviro
	Acute algae toxicity	ErC50 mg/l	16,47	96 h	Green algae	United States Environmental Protection A
	Acute crustacea toxicity	EC50 mg/l	46,6	48 h	Daphnid no other information.	United States Environmental Protection A
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics					
	Acute fish toxicity	LC50 mg/l	3 - 10	96 h	Oncorhynchus mykiss	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Raphidocelis subcapitata	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	4,6 - 10	48 h	Daphnia magna	OECD Guideline 202
	Fish toxicity	NOEC mg/l	(0,57)	28 d	Oncorhynchus mykiss	ECHA
	Algae toxicity	NOEC	(10) mg/l	3 d	Pseudokirchneriella subcapitata	
	Crustacea toxicity	NOEC	(1) mg/l	21 d	Daphnia magna	OECD Guideline 211
68937-41-7	Isopropylphenyl phosphate					
	Acute fish toxicity	LC50 mg/l	50,1	96 h	Pimephales promelas	ECHA
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 9 of 12

	Fish toxicity	NOEC 0,0031 mg/l	33 d	Pimephales promelas	OECD Guideline 210	
	Crustacea toxicity	NOEC 0,0415 mg/l	21 d	Daphnia magna	OECD Guideline 211	
	Acute bacteria toxicity	(> 1000 mg/l)	3 h	activated sludge, domestic	OECD Guideline 209	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)			
	Biodegradation	80%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
	Biodegradation	74,7%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics			
	Biodegradation	98%	28	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	4,2-7,2
106-97-8	butane	1,81
74-98-6	propane	1,81

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 10 of 12

same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 11 of 12

14.3. Transport hazard class(es): 2.1**14.4. Packing group:** -

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 98,855 % (672,213 g/l)

2004/42/EC (VOC): 98,855 % (672,213 g/l)

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1, 15, 16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

Innotech Feuchtigkeitsschutz & Pflegefluid PLUS 840

Revision date: 23.05.2018

Page 12 of 12

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT RE 1; H372	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)