



Metal-Free Mounting Paste 350

The specially micronised, white multi-purpose paste.

Properties:

- ▶ ideal for stainless steel and all metals
- ▶ solid particles in platelet form, embedded in synthetic oil
- ▶ prevents corrosion
- ▶ extremely high pressure absorption capacity
- ▶ water-resistant and chemically stable
- ▶ temperature range: -30 °C to +350 °C (dynamic)
- ▶ dry film up to 1450 °C

Application range:

- ▶ facilitates the dismantling of stainless steel connections
- ▶ on screwed and plug-in connections
- ▶ on plain bearings, wedge profiles, shafts and bushes
- ▶ on screwed connections in sewage treatment plants
- ▶ on sluice gates and barrages
- ▶ **Do not use on acetylene and oxygen systems**





Technical data

	Specific value	Unit	Testing method
Colour:	white		visual
Consistency provider:	inorganic		
Base oil:	synthetic oil		
Density 15 °C:	1.3	g/cm ³	DIN 51 757
Drip point:	without	°C	DIN ISO 2176
Solid lubricant:	white / approx. 50	weight %	
Resistance to cold:	-30	°C	CDB stir test
Consistency class:	1-2	NLGI No.	DIN 51 818
Temperature range:	-30 to +350 thin film lubrication	°C	
Corrosion protection SKF Emcor test:	no corrosion		DIN 51 802
High-pressure characteristics:	5,000 (four-ball test load) 20,000 (AWM test load)	N	DIN 51 350
Water resistance at 20/50/90 °C:	resistant		DIN 51 807

This information has been carefully compiled and reflects the current state of technical development. We reserve the right to make changes in the interest of progress. No liabilities of any kind can be derived from it.

Ordering information

Single unit	Container form*	Order No.
500 ml spray can	1 carton = 12 cans	03-116001
500 g tin	1 carton = 12 cans	03-116002
1 kg	1 tin	03-116003
20 kg	1 drum	03-116020

*other containers available on request

