

Telefax: +49 (0) 941 70 46 60

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Innotech Hochleistungsfett WDT 500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

lubricant

For use in industrial installations and professional treatment only.

1.3. Details of the supplier of the safety data sheet

Company name: innotech-Vertriebs GmbH

Street: Junkerstrasse 16
Place: D-93055 Regensburg
Telephone: +49 (0) 941 70 08 78

e-mail: info@innotech-r.de
Contact person: Mr. Massen
Internet: www.innotech-r.de
Responsible Department: sales department

1.4. Emergency telephone +49 (0) 941 70 08 78

number: Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contens/container to in accordance with local/regional/national/international

regulation.

2.3. Other hazards

No information available.



Print date: 12.11.2019

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 2 of 10

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts				
	271-529-4		01-2119492627-25		
	Eye Irrit. 2; H319				
61789-86-4	Ca-Salze, Sulfonsäuren, petroleum		<2,5 %		
	263-093-9		01-2119488992-18		
	Eye Irrit. 2; H319				
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts				
	274-263-7		01-2119492616-28		
	Skin Sens. 1, Aquatic Chronic 4; H317 H413				

Full text of H and EUH statements: see section 16.

Further Information

mineral oel with <3%DMSO-extract according IP 346

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), ABC-powder, Foam, Water spray jet Co-ordinate fire-fighting measures to the fire surroundings.



Print date: 12.11.2019

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 3 of 10

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Non-flammable. Burning produces heavy smoke.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothes. Use personal protection equipment. Special danger of slipping by leaking/spilling product.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

lubricant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



Print date: 12.11.2019

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 4 of 10

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts				
Worker DNEL,	long-term	inhalation	systemic	11,75 mg/m³	
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day	
Worker DNEL,	long-term	dermal	local	1,03 mg/cm ²	
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m³	
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day	
Consumer DNEL, long-term		dermal	local	0,513 mg/cm ²	
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day	

PNEC values

CAS No	Substance		
Environmental compartment		Value	
61789-86-4	Ca-Salze, Sulfonsäuren, petroleum		
Freshwater		1 mg/l	
Freshwater (in	termittent releases)	10 mg/l	
Marine water		1 mg/l	
Freshwater se	diment	226000000 mg/kg	
Marine sedime	nt	226000000 mg/kg	
Secondary poisoning		16,667 mg/kg	
Micro-organisms in sewage treatment plants (STP)		1000 mg/l	
Soil		271000000 mg/kg	
70024-69-0	9-0 Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts		
Freshwater 1		1 mg/l	
Freshwater (intermittent releases)		10 mg/l	
Marine water		1 mg/l	
Freshwater sediment		226000000 mg/kg	
Marine sediment		226000000 mg/kg	
Secondary poisoning		16,667 mg/kg	
Micro-organisms in sewage treatment plants (STP)		1000 mg/l	
Soil 27			

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: Eye glasses with side protection (DIN EN 166)



according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 5 of 10

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: FKM (fluoro rubber), NBR (Nitrile rubber) (EN ISO 374)

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

Usually no personal respirative protection necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste Colour: beige

Odour: like: Mineral oil

Test method

Print date: 12.11.2019

pH-Value: not relevant

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Flash point:

not relevant

> 200 °C

Flammability

Solid: not determined
Gas: not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

not applicable

not applicable

Auto-ignition temperature ASTM E659

Solid: >250 °C
Gas: not applicable
Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure:

Density (at 20 °C):

Water solubility:

No information available.

0,9 g/cm³

practically insoluble

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined



Print date: 12.11.2019

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 6 of 10

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts					
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40	
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)	other: 40 CFR, Section 163.81-2, Federal	
61789-86-4	Ca-Salze, Sulfonsäuren, petroleum					
	oral	LD50 > 5000 mg/kg	Rat	Study report (1985)	OECD Guideline 401	
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts					
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)	other: 40 CFR, Section 163.81-2, Federal	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.



Print date: 12.11.2019

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 7 of 10

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts					
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Selenastrum capricornutum	EPA OTS 797.1050	
	Acute bacteria toxicity	(> 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewag	Study report (1994)	OECD Guideline 209
61789-86-4	Ca-Salze, Sulfonsäuren, petroleum					
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)	EPA OTS 797.1050
	Acute bacteria toxicity	(> 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewag	Study report (1994)	OECD Guideline 209
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts					
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	EPA OTS 797.1050
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	REACh Registration Dossier	EPA OTS 797.1300
	Acute bacteria toxicity	(> 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewag	Study report (1994)	OECD Guideline 209

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	> 4,46
61789-86-4	Ca-Salze, Sulfonsäuren, petroleum	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.



Print date: 12.11.2019

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 8 of 10

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

120112 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF

METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of

metals and plastics; spent waxes and fats; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



Print date: 12.11.2019

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 9 of 10

EU regulatory information

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,13,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container



Print date: 12.11.2019

according to Regulation (EC) No 1907/2006

Innotech Hochleistungsfett WDT 500

Revision date: 12.11.2019 Page 10 of 10

SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H413 May cause long lasting harmful effects to aquatic life.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)