

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Innotech Synthetische Innenlagerschmierung 105

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Aerosol - Lubricants, greases, release products

Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the safety data sheet

Company name: innotech-Vertriebs GmbH

Street: Junkerstrasse 16

Place: D-93055 Regensburg

Telephone: +49 (0) 941 70 08 78

Telefax: +49 (0) 941 70 46 60

e-mail: info@innotech-r.de

Contact person: Mr. Massen

Internet: www.innotech-r.de

Responsible Department: sales department

1.4. Emergency telephone

+49 (0) 941 70 08 78

number:

Only available during office hours.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

according to Regulation (EC) No 1907/2006

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 2 of 15

P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with local/regional/national/international regulation.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			45 - < 50 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
106-97-8	Butane			20 - < 25 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	Propane			10 - < 12.5 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			2.5 - < 5 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
68937-41-7	Phenol, isopropylated, phosphate (3:1)			0.1 - < 0.5 %
	273-066-3		01-2119535109-41	
	Repr. 2, STOT RE 2, Aquatic Chronic 2; H361fd H373 H411			
61791-55-7	N-Tallow propylene diamine			0.1 - < 0.5 %
	263-189-0		01-2119487014-41	
	Acute Tox. 4, Skin Corr. 1B, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 2; H302 H314 H372 H400 H411			
115-86-6	Triphenyl phosphate			0.1 - < 0.5 %
	204-112-2		01-2119457432-41	
	Aquatic Chronic 1; H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 3 of 15

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 4 of 15

Advice on safe handling

Do not pierce or burn, even after use.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Aerosol - Lubricants, greases, release products

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
115-86-6	Triphenyl phosphate	-	3		TWA (8 h)	WEL
		-	6		STEL (15 min)	WEL

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 5 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
68937-41-7	Phenol, isopropylated, phosphate (3:1)			
Worker DNEL, long-term		inhalation	systemic	0,145 mg/m³
Worker DNEL, acute		inhalation	systemic	700 mg/m³
Worker DNEL, long-term		dermal	systemic	0,416 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	2000 mg/kg bw/day
Worker DNEL, acute		dermal	local	16 mg/cm²
Consumer DNEL, acute		inhalation	systemic	350 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,208 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	100 mg/kg bw/day
Consumer DNEL, acute		dermal	local	8 mg/cm²
Consumer DNEL, long-term		oral	systemic	0,04 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	50 mg/kg bw/day
115-86-6	Triphenyl phosphate			
Worker DNEL, long-term		inhalation	systemic	5,2 mg/m³
Worker DNEL, long-term		dermal	systemic	5,55 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,9 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,98 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,5 mg/kg bw/day

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 6 of 15

PNEC values

CAS No	Substance	
Environmental compartment		Value
68937-41-7	Phenol, isopropylated, phosphate (3:1)	
Freshwater		0 mg/l
Freshwater (intermittent releases)		0,015 mg/l
Marine water		0 mg/l
Freshwater sediment		0,185 mg/kg
Marine sediment		0,018 mg/kg
Secondary poisoning		1,85 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		2,5 mg/kg
115-86-6	Triphenyl phosphate	
Freshwater		0,004 mg/l
Freshwater (intermittent releases)		0,003 mg/l
Marine water		0 mg/l
Freshwater sediment		1,103 mg/kg
Marine sediment		0,11 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		5 mg/l
Soil		0,218 mg/kg

8.2. Exposure controls**Protective and hygiene measures**

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: Eye glasses with side protection DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber) EN ISO 374

Thickness of the glove material: $\geq 0,4\text{mm}$.

Breakthrough time (maximum wearing time): 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus:

Combination filtering device (EN 14387) AX-P2

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 7 of 15

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light yellow
Odour:	like: lubricant, gun-oil and gun-cleaner, rust protection

Test method

pH-Value:	not applicable
-----------	----------------

Changes in the physical state

Melting point:	not applicable
Initial boiling point and boiling range:	< -20 °C
Flash point:	< -20 °C
Sustaining combustion:	No data available

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

Heating may cause an explosion. In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	15 vol. %
Ignition temperature:	> 200 °C

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	not determined
----------------------------	----------------

Oxidizing properties

Not oxidising.

Vapour pressure:	not determined
------------------	----------------

Density (at 20 °C):	0,685 g/cm ³ calculated.
---------------------	-------------------------------------

Water solubility: (at 20 °C)	practically insoluble
---------------------------------	-----------------------

Solubility in other solvents

not determined

Partition coefficient:	not determined
------------------------	----------------

Viscosity / dynamic:	not applicable
----------------------	----------------

Vapour density:	not determined
-----------------	----------------

Evaporation rate:	not determined
-------------------	----------------

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol.

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 8 of 15

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat	OECD 403	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 16 mg/l	Rat	Toxicology and Applied Pharmacology 32:	OECD Guideline 403
68937-41-7	Phenol, isopropylated, phosphate (3:1)				
	dermal	LD50 > 10000 mg/kg	Rabbit	Study report (1976)	other: 16 CFR 1500.40
61791-55-7	N-Tallow propylene diamine				
	oral	ATE 500 mg/kg			
115-86-6	Triphenyl phosphate				
	oral	LD50 > 20000 mg/kg	Rat	Study report (1976)	OECD Guideline 401
	dermal	LD50 > 10000 mg/kg	Rabbit	Study report (1976)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 9 of 15

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 10 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	OECD Guideline 202	
	Fish toxicity	NOEC 0,101 mg/l	28 d	Oncorhynchus mykiss	REACH Registration Dossier	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 0,176 mg/l	21 d	Daphnia magna	REACH Registration Dossier	The aquatic toxicity was estimated by a
106-97-8	Butane					
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
74-98-6	Propane					
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
	Acute fish toxicity	LC50 3 - 10 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203	
	Acute algae toxicity	ErC50 10 - 30 mg/l	72 h	Raphidocelis subcapitata	OECD Guideline 201	
	Acute crustacea toxicity	EC50 7,4 mg/l	48 h	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 202
	Fish toxicity	NOEC 0,574 mg/l	28 d	Oncorhynchus mykiss	Hydrocarbon Solvents Consortium SEIF (HS	The aquatic toxicity was estimated by a
	Algae toxicity	NOEC (10) mg/l	3 d	Pseudokirchneriella subcapitata		
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 11 of 15

68937-41-7	Phenol, isopropylated, phosphate (3:1)						
	Acute fish toxicity	LC50	10,8	96 h	Pimephales promelas	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50	> 2,5	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50	1,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Fish toxicity	NOEC	0,0031	33 d	Pimephales promelas	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC	0,0415	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	(> 1000 mg/l)		3 h	activated sludge, domestic	REACH Registration Dossier	OECD Guideline 209
115-86-6	Triphenyl phosphate						
	Acute fish toxicity	LC50	0,4 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	other: see below
	Acute algae toxicity	ErC50	2,45	72 h	Pseudokirchneriella subcapitata	Study report (2000)	OECD Guideline 201
	Acute crustacea toxicity	EC50	1 mg/l	48 h	Daphnia magna	Aquatic Toxicology and Hazard Assessment	other: see below
	Fish toxicity	NOEC	>= 0,001	90 d	Oncorhynchus mykiss	Aquatic Toxicology and Hazard Assessment	Flow through system with 90d exposure pe
	Crustacea toxicity	NOEC	0,254	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
	Biodegradation	80%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
	Biodegradation	98%	28	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 12 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	Butane	1,09
74-98-6	Propane	1,09
68937-41-7	Phenol, isopropylated, phosphate (3:1)	85000 - 150000
115-86-6	Triphenyl phosphate	4,63

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	144,3	calculated	Other company data (
68937-41-7	Phenol, isopropylated, phosphate (3:1)	225	Lepomis macrochirus	REACH Registration D
115-86-6	Triphenyl phosphate	144	Oryzias latipes	REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1



Classification code: 5F

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 13 of 15

Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203

according to Regulation (EC) No 1907/2006

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 14 of 15

IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC):	88,341 % (605,135 g/l)
2004/42/EC (VOC):	88,347 % (605,177 g/l)
Information according to 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS

Additional informationTo follow: 850/2004/EC, 79/117/EEC, 689/2008/EC , 2008/47/EC
Aerosol directive (75/324/EEC).**National regulatory information**

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,9,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%

Innotech Synthetische Innenlagerschmierung 105

Revision date: 27.06.2019

Page 15 of 15

EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)