



Schutz-Wachs 810

Pioneering - Sustainable - Tried and tested

810



Protective Wax 810
Highly adhesive, pressure-resistant and elastic corrosion protection.

Properties:

- ▶ excellent water resistance
- ▶ pressure-resistant
- ▶ very good adhesion
- ▶ elastic protective film
- ▶ no dripping in sunlight
- ▶ good penetration capacity
- ▶ corrosion protection during outdoor exposure:
2 years

Application range:

- ▶ for the protection of injection moulds
- ▶ for cavity sealing on machines
- ▶ for corrosion protection on open glide points





Technical data

	Specific value	Unit	Testing method
Colour:	light-brown, clear		visual
Density 20 °C:	0.881	g/cm ³	DIN 51 757
Drying time:	15–20	minutes	
Viscosity 20 °C:	14	4mm nozzle (Ford cup)	DIN 51 550
Drip point:	without		
Application range:	-40 bis +120	°C	
Corrosion protection	up to 2 years for outdoor exposure		
Salt spray test:	120 (very good)	hours	

This information has been carefully compiled and reflects the current state of technical development. We reserve the right to make changes in the interest of progress. No liabilities of any kind can be derived from it.

Ordering information

Single unit	Container form*	Order No.
500 ml spray can	1 carton = 12 cans	03-810 001
20 litres	Plastic canister	03-810 020

*other containers available on request

