

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricants, greases, release products

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: innotech-Vertriebs GmbH

Street: Junkerstrasse 16

Place: D-93055 Regensburg

Telephone: +49 (0) 941 70 08 78

Telefax: +49 (0) 941 70 46 60

e-mail: info@innotech-r.de

Contact person: Mr. Massen

Internet: www.innotech-r.de

Responsible Department: sales department

1.4. Emergency telephone

+49 (0) 941 70 08 78

number:

Only available during office hours.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 3

Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - repeated exposure: STOT RE 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics

Signal word: Danger**Pictograms:****Hazard statements**

H226

Flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H372

Causes damage to organs through prolonged or repeated exposure.

H412

Harmful to aquatic life with long lasting effects.

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 2 of 12

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P331 Do NOT induce vomiting.
- P370+P378 In case of fire: Use Carbon dioxide (CO₂), Foam, Extinguishing powder to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

- EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

In use may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)			45 - < 50 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			40 - < 45 %
	919-164-8		01-2119473977-17	
	STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H372 H304 H412 EUH066			
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics			10 - < 12.5 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
68937-41-7	Isopropylphenyl phosphate			0.1 - < 0.5 %
	273-066-3		01-2119535109-41	
	Repr. 2, STOT RE 2, Aquatic Chronic 2; H361fd H373 H411			
61791-55-7	N-Tallow propylene diamine			0.1 - < 0.5 %
	263-189-0		01-2119487014-41	
	Acute Tox. 4, Skin Corr. 1B, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 2; H302 H314 H372 H400 H411			
115-86-6	Triphenyl phosphate			0.1 - < 0.5 %
	204-112-2			
	Aquatic Chronic 1; H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down. If unconscious place in recovery position and seek medical advice.

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 3 of 12

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Wash with plenty of water. Immediately remove any contaminated clothing, shoes or stockings. Medical treatment necessary.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not unconscious. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 4 of 12

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Lubricants, greases, release products
Reserved for industrial and professional use.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
115-86-6	Triphenyl phosphate	-	3		TWA (8 h)	WEL
		-	6		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics			
Worker DNEL, long-term	dermal		systemic	773 mg/kg bw/day
Worker DNEL, long-term	inhalation		systemic	2035 mg/m ³
Consumer DNEL, long-term	dermal		systemic	699 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	608 mg/m ³
Consumer DNEL, long-term	oral		systemic	699 mg/kg bw/day

8.2. Exposure controls**Appropriate engineering controls**

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 5 of 12

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: Eye glasses with side protection DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber) DIN EN 374

Thickness of the glove material: $\geq 0,4$ mm

Breakthrough time (maximum wearing time): 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus:

Combination filtering device (EN 14387) A-P2.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light yellow
Odour:	like: Mineral oil
pH-Value:	not applicable

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	90 °C
Flash point:	33 °C
Sustaining combustion:	No data available

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

In use may form flammable/explosive vapour-air mixture.

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	7 vol. %
Ignition temperature:	> 200 °C

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	4 hPa
Density (at 20 °C):	0,8 g/cm ³

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 6 of 12

Water solubility: practically insoluble
(at 20 °C)

Solubility in other solvents
not determined

Partition coefficient: not determined

Viscosity / kinematic: 1,4 mm²/s
(at 40 °C)

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)				
	oral	LD50 > 15000 mg/kg	Rat	OECD Guideline 423	
	dermal	LD50 >= 3160 mg/kg	Rabbit	OECD Guideline 402	
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat	OECD 403	
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >3400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 (13,1) mg/l	Rat		
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2800 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >23,3 mg/l	Rat		
68937-41-7	Isopropylphenyl phosphate				
	dermal	LD50 > 10000 mg/kg	Rabbit	16 CFR 1500. 40	
61791-55-7	N-Tallow propylene diamine				
	oral	ATE 500 mg/kg			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking. Causes damage to organs through prolonged or repeated exposure. (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

Aspiration hazard

May be fatal if swallowed and enters airways. (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%); Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics)

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information**12.1. Toxicity**

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 8 of 12

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201	
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	OECD Guideline 202	
	Fish toxicity	NOEC (0,101) mg/l	28 d	Oncorhynchus mykiss	ECHA	
	Crustacea toxicity	NOEC (0,176) mg/l	21 d	Daphnia magna	ECHA	
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)					
	Acute fish toxicity	LC50 10-100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 50-100 mg/l	72 h	Pseudokirchnerella subcapitata		
	Acute crustacea toxicity	EC50 10-22 mg/l	48 h	Daphnia magna (Big water flea)		
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics					
	Acute fish toxicity	LC50 3 - 10 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203	
	Acute algae toxicity	ErC50 10 - 30 mg/l	72 h	Raphidocelis subcapitata	OECD Guideline 201	
	Acute crustacea toxicity	EC50 4,6 - 10 mg/l	48 h	Daphnia magna	OECD Guideline 202	
	Fish toxicity	NOEC (0,57) mg/l	28 d	Oncorhynchus mykiss	ECHA	
	Algae toxicity	NOEC (10) mg/l	3 d	Pseudokirchnerella subcapitata		
	Crustacea toxicity	NOEC (1) mg/l	21 d	Daphnia magna	OECD Guideline 211	
68937-41-7	Isopropylphenyl phosphate					
	Acute fish toxicity	LC50 50,1 mg/l	96 h	Pimephales promelas	ECHA	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201	
	Fish toxicity	NOEC 0,0031 mg/l	33 d	Pimephales promelas	OECD Guideline 210	
	Crustacea toxicity	NOEC 0,0415 mg/l	21 d	Daphnia magna	OECD Guideline 211	
	Acute bacteria toxicity	(> 1000 mg/l)	3 h	activated sludge, domestic	OECD Guideline 209	

12.2. Persistence and degradability

The product has not been tested.

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 9 of 12

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%)			
	Biodegradation	80%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
	Biodegradation	74,7%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons C7-C9, n-Alkanes, Isoalkanes, Cyclics			
	Biodegradation	98%	28	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	4,2-7,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%); Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

14.3. Transport hazard class(es):

3

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 10 of 12

14.4. Packing group:

III

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640E

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

30

Tunnel restriction code:

D/E

Inland waterways transport (ADN)**14.1. UN number:**

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%); Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640E

Limited quantity:

5 L

Excepted quantity:

E1

Marine transport (IMDG)**14.1. UN number:**

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%); Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); HYDROCARBONS, LIQUID, N.O.S.)

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Special Provisions:

223, 274, 955

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-E, S-E

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:**

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (<2%); Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

14.3. Transport hazard class(es):

3

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 11 of 12

14.4. Packing group:

III

Hazard label:

3



Special Provisions:

A3

Limited quantity Passenger:

10 L

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

yes



Danger releasing substance:

HYDROCARBONS, LIQUID, N.O.S.

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 98,188 % (785,504 g/l)

2004/42/EC (VOC): 98,188 % (785,504 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D):

2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

Innotech Feuchtigkeitsschutz & Pflegefluid 840 (flüssig)

Revision date: 13.07.2018

Page 12 of 12

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)