



Clear Chain and Cable Grease 135

Pioneering - Sustainable - Tried and tested

135



Clear Chain and Cable Grease 135
The fully synthetic special oil for extreme conditions and high temperatures.



Properties:

- ▶ excellent high-temperature performance up to +250 °C
- ▶ very high stress resistance
- ▶ extraordinary adhesive strength
- ▶ chemically stable and resistant to ageing
- ▶ salt and hot water resistant
- ▶ neutral to high-quality sealing materials
- ▶ reliable corrosion protection
- ▶ silicone-free

Application range:

- ▶ for drive, transport and conveyor chains, cables, gears and spindles under extreme pressure loads and in wet environments
- ▶ for locks, port and shipyard facilities
- ▶ in sewage treatment plants and power stations
- ▶ in the glass, ceramics and metal industries
- ▶ in paper and plastics processing
- ▶ for stretching and drying frames in the textile industry





Technical data

	Specific value	Unit	Testing method
Colour:	reddish		visual
Appearance:	clear		visual
Flash point:	260	°C	DIN ISO 2592
Density 20 °C:	0,920	g/cm ³	DIN 51 757
Kinematic viscosity (40 °C):	3800	mm ² /s	DIN 51 550
Temperature application range:	-10 to +250	°C	
Four-ball welding force	4200	N	Four-ball test
Solubility in water:	not soluble		
Pourpoint:	< -10	°C	DIN ISO 3016

This information has been carefully compiled and reflects the current state of technical development. We reserve the right to make changes in the interest of progress. No liabilities of any kind can be derived from it.

Ordering information

Single unit	Container form*	Order No.
500 ml spray can	1 carton = 12 cans	03-450001
5 litres	Plastic canister	03-450005
20 litres	Plastic canister	03-450020
200 litres	Metal drum	03-450200

*other containers available on request

