

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Innotech Schnellentfetter 200ml, 500ml

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**Aerosol - Washing and cleaning products
Professional uses**1.3. Details of the supplier of the safety data sheet**

Company name:	innotech-Vertriebs GmbH	
Street:	Junkerstrasse 16	
Place:	D-93055 Regensburg	
Telephone:	+49 (0) 941 70 08 78	Telefax: +49 (0) 941 70 46 60
e-mail:	info@innotech-r.de	
Contact person:	Mr. Massen	
Internet:	www.innotech-r.de	
Responsible Department:	sales department	

1.4. Emergency telephone number: +49 (0) 941 70 08 78
Only available during office hours.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Aerosol: Aerosol 1
Aspiration hazard: Asp. Tox. 1
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
May be fatal if swallowed and enters airways.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Acetone
propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger**Pictograms:**

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 2 of 14

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			35 - < 40 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
67-64-1	Acetone			25 - < 30 %
	200-662-2		01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			25 - < 30 %
	200-661-7		01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
124-38-9	Carbondioxide			2.5 - < 5 %
	204-696-9			
	Compressed gas; H280			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data)

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 3 of 14

sheet if possible).

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Headache, Dizziness, Nausea

After ingestion: Subsequent observance for pneumonia and lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 4 of 14

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use. Do not breathe gas/fumes/vapour/spray. Use only outdoors or in a well-ventilated area.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Aerosol - Washing and cleaning products

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 5 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
67-64-1	Acetone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	500 mg/m³
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
67-64-1	Acetone	
Freshwater	10,6 mg/l	
Marine water	1,06 mg/l	
Freshwater sediment	30,4 mg/kg	
Marine sediment	3,04 mg/kg	
Soil	29,5 mg/kg	
Freshwater (intermittent releases)	21 mg/l	
Micro-organisms in sewage treatment plants (STP)	100 mg/l	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater	140,9 mg/l	
Freshwater (intermittent releases)	140,9 mg/l	
Marine water	140,9 mg/l	
Freshwater sediment	552 mg/kg	
Marine sediment	552 mg/kg	
Secondary poisoning	160 mg/kg	
Micro-organisms in sewage treatment plants (STP)	2251 mg/l	
Soil	28 mg/kg	

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 6 of 14

8.2. Exposure controls**Appropriate engineering controls**

Do not breathe gas/fumes/vapour/spray. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: goggles. DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. EN ISO 374
Suitable material: NBR (Nitrile rubber) (0,4 mm), FKM (fluoro rubber) (0,7 mm), Breakthrough time (maximum wearing time): >480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection**Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus:
Combination filtering device (EN 14387) A-P2

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like:Solvent
pH-Value:	not applicable

Changes in the physical state

Melting point:	not applicable
Initial boiling point and boiling range:	56 °C
Flash point:	< 0 °C
Sustaining combustion:	No data available

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

Heating may cause an explosion. In use may form flammable/explosive vapour-air mixture.

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	13 vol. %
Ignition temperature:	>200 °C

Auto-ignition temperature

Solid:	not applicable
--------	----------------

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 7 of 14

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,75 g/cm³Water solubility:
(at 20 °C) partially miscible**Solubility in other solvents**

not determined

Partition coefficient: not determined

Viscosity / dynamic: not applicable

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 8 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 16 mg/l	Rat	Toxicology and Applied Pharmacology 32:	OECD Guideline 403
67-64-1	Acetone				
	oral	LD50 5800 mg/kg	Rat	J Toxicol Environ Health 15: 609-621 (19)	Undiluted acetone applied to female rats
	dermal	LD50 > 7426 mg/kg	Rabbit	Toxicol Appl Pharmacol 7: 559-565. (1965)	other: Code of federal regulations: 21 C
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 4570 mg/kg	Rat		
	dermal	LD50 13400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 30 mg/l	Rat		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; Acetone; propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 9 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
	Acute fish toxicity	LC50 mg/l	3 - 10	96 h	Oncorhynchus mykiss	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Raphidocelis subcapitata	OECD Guideline 201
	Acute crustacea toxicity	EC50	7,4 mg/l	48 h	Daphnia magna	SIDS Initial Assessment Report For SIAM
	Fish toxicity	NOEC mg/l	0,574	28 d	Oncorhynchus mykiss	Hydrocarbon Solvents Consortium SEIF (HS)
	Algae toxicity	NOEC	(10) mg/l	3 d	Pseudokirchneriella subcapitata	
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM
67-64-1	Acetone					
	Acute fish toxicity	LC50 mg/l	8120	96 h	Pimephales promelas	Publication (1984)
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia pulex	Publication (1978)
	Algae toxicity	NOEC	430 mg/l	4 d		
	Crustacea toxicity	NOEC mg/l	2212	28 d	Daphnia magna	Arch Environm Contam Toxicol 12: 305-310
	Acute bacteria toxicity	(61150 mg/l)		0,5 h	activated sludge of a predominantly domestic sewage	Water Res 26: 887-892 (1992)
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	(>100 mg/l)				
124-38-9	Carbondioxide					
	Acute fish toxicity	LC50	35 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	

12.2. Persistence and degradability

The product has not been tested.

according to Regulation (EC) No 1907/2006

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 10 of 14

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
	Biodegradation	98%	28	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D
	Readily biodegradable (according to OECD criteria).			
67-64-1	Acetone			
	Biodegradation	91%	28	
	Readily biodegradable (according to OECD criteria).			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	Biodegradation	95%	21	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	Acetone	-0,23
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	Acetone	3		Unpublished calculat

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

according to Regulation (EC) No 1907/2006

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 11 of 14

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1

according to Regulation (EC) No 1907/2006

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 12 of 14



Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Hydrocarbons, C7-C9, n-al

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC):	96 % (720 g/l)
2004/42/EC (VOC):	96 % (720 g/l)
Information according to 2012/18/EU (SEVESO III):	E2 Hazardous to the Aquatic Environment
Additional information:	P3b

Additional information

Regulation (EC) No. 648/2004 (Detergents regulation). To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC , 2008/47/EC
 Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,4,6,7,8,9,12,14,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 13 of 14

IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H229 Pressurised container: May burst if heated.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Innotech Schnellentfetter 200ml, 500ml

Revision date: 27.06.2019

Page 14 of 14

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)